

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

SECTION 1: Identification

Product Identifier

Product Name: Bay and Wall Cleaner Product code: ST-275

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Not determined or not applicable. Uses Advised Against: Not determined or not applicable. Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: United States JBS Industries 2726 Henkle Drive Lebanon, Ohio 45036 513-228-2800 SBAETEN@JBSINDUSTRIES.COM

Emergency Telephone Number:

SECTION 2: Hazard(s) Identification

GHS Classification:

Corrosive to metals, category 1 Skin corrosion, category 1A Serious eye damage, category 1 Specific target organ toxicity - single exposure, category 3, respiratory tract irritation Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

Precautionary Statements:

P234 Keep only in original container P260 Do not breathe dust/fume/gas/mist/vapors/spray Page 1 of 18

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

P264 Wash hands thoroughly after handling P280 Wear protective gloves/protective clothing/eye protection/face protection P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area P390 Absorb spillage to prevent material-damage P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P363 Wash contaminated clothing before reuse P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P310 Immediately call a POISON CENTER/doctor/... P321 Specific treatment (see ... on this label) P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 Call a POISON CENTER/doctor/.../if you feel unwell P406 Store in corrosive resistant/... container with a resistant inner liner P405 Store locked up P403+P233 Store in a well-ventilated place. Keep container tightly closed P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 68439-46-3	Alcohols, C9-11, branched and linear, ethoxylated	<90
CAS Number: 111-76-2	2-Butoxyethanol	<20
CAS Number: 68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	<95
CAS Number: 7664-38-2	Orthophosphoric Acid	<85
CAS Number: 77-92-9	Citric acid	
CAS Number: 1300-72-7	Sodium Xylenesulfonate <4	
CAS Number: 7647-01-0	Hydrogen chloride <37	
CAS Number: 75-21-8	r: Ethylene oxide <0	
CAS Number: 123-91-1	1,4-dioxane <	
CAS Number: 107-21-1	Ethane-1,2-diol	

Additional Information: None

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023 Revision date: 03.08.2023

Bay and Wall Cleaner

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Products that are corrosive to metals are often corrosive to the skin, eyes and the respiratory tract. Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

result in respiratory distress, confusion and unconsciousness.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

If respiratory symptoms persist, seek medical attention.

Overexposure via inhalation requires urgent medical treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Contact with metals may evolve flammable hydrogen gas. Thermal decomposition may produce irritating/toxic fumes/gases.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

DO NOT GET WATER INSIDE CONTAINERS. Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023 Revision date: 03.08.2023

Bay and Wall Cleaner

clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable corrosive resistant containers for future disposal. Do not get water in containers as reaction with water or moist air may release toxic, corrosive or flammable gases. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Orthophosphoric Acid	7664-38-2	8-Hour TWA: 1 mg/m³
	Orthophosphoric Acid	7664-38-2	15-Minute STEL: 3 mg/m ³

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Country (Legal Basis)	Substance	Identifier	Permissible concentration	
	Hydrogen chloride	7647-01-0	Ceiling Limit: 2 ppm	
	Ethane-1,2-diol	107-21-1	8-Hour TWA: 25 ppm (vapor fraction)	
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 50 ppm (vapor fraction)	
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 10 mg/m ³ (aerosol only, inhalable fraction)	
	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm	
	Ethylene oxide	75-21-8	TWA: 1 ppm	
	1,4-dioxane	123-91-1	TLV-TWA: 20 ppm (8 hr)	
NIOSH	Orthophosphoric Acid	7664-38-2	REL-TWA: 1 mg/m ³ (up to 10 hr)	
	Orthophosphoric Acid	7664-38-2	STEL: 3 mg/m ³	
	Orthophosphoric Acid	7664-38-2	IDLH: 1000 mg/m ³	
	Hydrogen chloride	7647-01-0	Ceiling Limit: 7 mg/m ³ (5 ppm)	
	Hydrogen chloride	7647-01-0	IDLH: 50 ppm	
	2-Butoxyethanol	111-76-2	IDLH: 700 ppm	
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m ³ (5 ppm [up to 10 hr])	
	Ethylene oxide	75-21-8	IDLH: 800 ppm	
	Ethylene oxide 75-21-8		Ceiling Limit: 9 mg/m ³ (5 ppm [10-min/day])	
	Ethylene oxide	75-21-8	REL: 0.18 mg/m ³ (0.1 ppm)	
	1,4-dioxane	123-91-1	Ceiling Limit: 3.6 mg/m ³ (1 ppm [30-min])	
	1,4-dioxane	123-91-1	IDLH: 500 ppm	
OSHA	Orthophosphoric Acid	7664-38-2	8-Hour TWA-PEL: 1 mg/m ³	
	Hydrogen chloride	7647-01-0	Ceiling Limit: 7 mg/m ³ (5 ppm)	
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m ³ (50 ppm)	
	Ethylene oxide	75-21-8	TWA: 1 ppm	
	Ethylene oxide	75-21-8	STEL: 5 ppm	
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 360 mg/m ³ (100 ppm [Table Z-1])	
	1,4-dioxane	123-91-1	TWA: 90 mg/m³ (25 ppm [Table Z-1-A])	
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 125 mg/m³ (50 ppm)	
United States(California)	Orthophosphoric Acid	7664-38-2	8-Hour TWA-PEL: 1 mg/m ³	
	Orthophosphoric Acid	7664-38-2	15-Minute STEL: 3 mg/m ³	
	Hydrogen chloride	7647-01-0	8-Hour TWA: 0.3 ppm	
	Hydrogen chloride	7647-01-0	Ceiling Limit: 2 ppm	
	2-Butoxyethanol	xyethanol 111-76-2 8-Hour TWA-PI (20 ppm)		
	Ethylene oxide	75-21-8	STEL: 5 ppm	
	Ethylene oxide	ne oxide 75-21-8 PEL: 2 mg/m ³ (

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Country (Legal Basis)	Substance I		Permissible concentration		
	Ethylene oxide	75-21-8	REL: 0.03 mg/m³ (Chronic inhalation)		
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 1 mg/m ³ (0.28 ppm)		
	1,4-dioxane	123-91-1	REL: 3000 ug/m ³ ([8 hr]; Acute inhalation)		
	1,4-dioxane	123-91-1	REL: 3000 ug/m³ ([8 hr]; Chronic inhalation)		
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 100 mg/m³ (40 ppm)		
	Ethane-1,2-diol	107-21-1	REL: 400 ug/m³ (Chronic Inhalation)		

Biological Limit Values:

Country (Legal Basis)	Substance	ldentifi er	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76- 2	Butoxyacetic acid (with hydrolysis)	Creatinine in Urine	End of shift	200 mg/g
	Ethylene oxide	75-21-8	N-(2- hydroxyethyl)- valine (HEV) hemoglobin adducts	Hemoglobin adducts	Not critical	5000 pmol/g
	Ethylene oxide	75-21-8	S-(2- hydroxyethyl) mercapturic acid (HEMA)	Creatinine in urine	End of shift	5 μg/g

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Not determined or not available.
Not determined or not available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Name	Route	Result
Citric acid	oral	LD50 Mouse: 5400 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
Orthophosphoric Acid	inhalation	LC50 Rat: 1.689 mg/L (1 hr)
	oral	LD50 Rat: 1530 mg/kg
	dermal	LD50 Rabbit: 2740 mg/kg
Hydrogen chloride	inhalation	LC50 Rat: 1562 ppmV (4 h [Gas])
	dermal	LD50 Rabbit: >5000 mg/m³
Ethane-1,2-diol	dermal	LD50 Mouse: > 3500 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg (Converted acute toxicity point estimate)
2-Butoxyethanol	dermal	LD50 Rabbit: 1060 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg (Annex VI to the CLP)
	oral	LD50 Rat: 470 mg/kg
	Inhalation ATE	LC50 Rat: 11 mg/L (4 hr [Vapor])
Ethylene oxide	Inhalation ATE	LC50 Rat: 700 ppmV ((Gases))
	Oral ATE	LD50 Rat: 100 mg/kg
1,4-dioxane	oral	LD50 Rat: 5150 mg/kg
	dermal	LD50 Rabbit: 7600 mg/kg
	inhalation	LC50 Rat: 9158 ppmV (4 hr [vapor])
Alcohols, C9-11, branched and	oral	LD50 Rat: 1378 mg/kg
linear, ethoxylated	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: >100 mg/m ³ (6 hr [Vapor; read-across])

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Name	Route	Result
Sodium Xylenesulfonate	dermal	LD50 Rabbit: >= 2000 mg/kg
	oral	LD50 Rat: >= 3346 mg/kg
Benzenesulfonic acid, C10-16-	inhalation	LC50 Rat: >1.9 mg/L (4 h [aerosol])
alkyl derivatives	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Orthophosphoric Acid	Causes severe skin burns.
Hydrogen chloride	Causes severe skin burns.
2-Butoxyethanol	Causes skin irritation.
Ethylene oxide	Causes severe skin burns.
Benzenesulfonic acid, C10-16- alkyl derivatives	Causes severe skins burns.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Citric acid	Causes serious eye irritation.
Orthophosphoric Acid	Causes serious eye damage.
Sodium Xylenesulfonate	Causes serious eye irritation.
Hydrogen chloride	Causes serious eye damage.
2-Butoxyethanol	Causes serious eye irritation.
Ethylene oxide	Causes serious eye damage.
1,4-dioxane	Causes serious eye irritation.
Alcohols, C9-11, branched and linear, ethoxylated	Causes serious eye damage.
Benzenesulfonic acid, C10-16- alkyl derivatives	Causes serious eye damage.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Revision date: 03.08.2023

Bay and Wall Cleaner

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Species	Result
Ethylene oxide		May cause cancer.
1,4-dioxane		May cause cancer. This substance is characterized as "likely to be carcinogenic to humans." This characterization is based on the following findings: (1) inadequate evidence of carcinogenicity in humans, and (2) sufficient evidence in animals (i.e., hepatic tumors in multiple species [three strains of rats, two strains of mouse, and in guinea pigs] mesotheliomas of the peritoneum, mammary, and nasal tumors have also been observed in rats following 2 years of oral exposure to this substance). U.S. Environmental Protection Agency's Integrated Risk Information System (IRIS).
Hydrogen chloride		Mists of this strong inorganic acids may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Citric acid	Not Applicable
Orthophosphoric Acid	Not Applicable
Hydrogen chloride	Group 3
Ethane-1,2-diol	Not Applicable
	Not Applicable
Ethylene oxide	Group 1
1,4-dioxane	Group 2B
Alcohols, C9-11, branched and linear, ethoxylated	Not Applicable
Sodium Xylenesulfonate	Not Applicable
2-Butoxyethanol	Group 3
Benzenesulfonic acid, C10-16- alkyl derivatives	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Citric acid	Not Applicable
Orthophosphoric Acid	Not Applicable
Hydrogen chloride	Not Applicable
Ethane-1,2-diol	Not Applicable
	Not Applicable
Ethylene oxide	Known to be human carcinogens
1,4-dioxane	Reasonably anticipated to be human carcinogens
Alcohols, C9-11, branched and linear, ethoxylated	Not Applicable
Sodium Xylenesulfonate	Not Applicable
2-Butoxyethanol	Not Applicable

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Name	Classification
Benzenesulfonic acid, C10-16- alkyl derivatives	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Ethylene oxide	May cause genetic defects.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Ethylene oxide	May damage fertility. Suspected of damaging the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause respiratory irritation.

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

Name	Result
Hydrogen chloride	May cause respiratory irritation.
Ethylene oxide	May cause respiratory irritation.
	May cause drowsiness or dizziness.
1,4-dioxane	May cause respiratory irritation.
Citric acid	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Name	Result
Orthophosphoric Acid	Repeated and/or prolonged exposure may have effects on the upper respiratory tract and lungs. This may result in chronic inflammation and reduced lung function.
Ethane-1,2-diol	May cause damage to Kidneys through prolonged or repeated Oral exposure.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023 Revision date: 03.08.2023

Bay and Wall Cleaner

Name	Result
	Studies on the effects of Ethylene oxide have concluded not only neurotoxic symptoms in humans, but also measured effects on nerve conduction velocities indicative of sensorimotor neuropathy, and axonal degeneration observed in nerve biopsies of exposed workers.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics: No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Name	Result
Citric acid	Fish LC50 Pimephales promelas: >100 mg/L (96 hr)
	Aquatic Invertebrates EC50 Dreissena polymorpha: >50 mg/L (48 hr)
Orthophosphoric Acid	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr [immobilization])
	Aquatic Plants EC50 Desmodesmus subspicatus: > 100 mg/L (72 hr [growth rate])
Hydrogen chloride	Aquatic Invertebrates LC50 Carcinus maenas: 240 mg/L (48 h)
Ethane-1,2-diol	Aquatic Plants EC50 Raphidocelis subcapitata: 6500 - 13,000 mg/L (96 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr)
	Fish LC50 Pimephales promelas: 72,860 mg/L (96 hr)
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr)
	Aquatic Plants EC50 Freshwater algae: 1840 mg/L (72 hr [growth rate])
Ethylene oxide	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 240 mg/L (96 h, read-across substance data)
	Aquatic Invertebrates LC50 Daphnia magna: 212 mg/L (48 h)
	Fish LC50 Pimephales promelas: 84 mg/L (96 h)
1,4-dioxane	Fish LC50 Pimephales promelas: 9850 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >1000 mg/L (48 hr)
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >1000 mg/L (72 hr)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Name	Result
Alcohols, C9-11, branched and linear, ethoxylated	Fish LC50 Oncorhynchus mykiss: 5 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 2.5 mg/L (48 hr)
	Aquatic Plants ErC50 Selenastrum capricornutum: 1.4 mg/L (96 hr)
Sodium Xylenesulfonate	Aquatic Plants EC50 Selenastrum capricornutum: >=758 mg/L (96 hr [growth rate; read-across])
	Fish LC50 Oncorhynchus mykiss: >=1580 mg/L (96 hr [read-across])
	Aquatic Invertebrates EC50 Daphnia magna: >1020 mg/L (48 hr [mobility; read-across])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
	Fish NOEC Menidia peninsulae: > 40 mg/L (28 d [mortality])
	Aquatic Invertebrates NOEC Daphnia magna: > 15,000 mg/L mg/L (21 d [reproduction])
2-Butoxyethanol	Fish LC50 Poecilia reticulata: 983 mg/L (7 d)
	Aquatic Invertebrates EC50 Daphnia magna: 297 mg/L (21 d [reproduction])
	Aquatic Plants NOEC Pseudokirchneriella subcapitata: 580 mg/L (72 hr)
	Fish NOEC Pimephales promelas: 145 mg/L (32 d)
	Aquatic Invertebrates NOEC Daphnia magna: 1000 mg/L (21 d)
Alcohols, C9-11, branched and linear, ethoxylated	Fish NOEC Lepomis macrochirus: > 0.33 mg/L (30 d)
	Aquatic Invertebrates NOEC Daphnia magna: 0.77 mg/L (21 d)

Persistence and Degradability

Product Data: No data available.

Name	Result
Citric acid	Readily biodegradable in water (97% degradation after 28 days).
Hydrogen chloride	Substance is non degradable and persistent in the aquatic and terrestrial environment.
Ethane-1,2-diol	Substance is readily biodegradable (90-100% degradation after 10 days in water by DOC removal).
2-Butoxyethanol	Readily biodegradable (90.4% degradation after 28 days, measured by CO2 evolution).
Ethylene oxide	Readily biodegradable (96% degradation after 28 days, measured by TOC removal).
1,4-dioxane	Not readily biodegradable (< 10 % degradation after 29 days).
Orthophosphoric Acid	Degradation studies are not applicable to inorganic substances.
Sodium Xylenesulfonate	The substance is readily biodegradable. 83 - 85% degradation, measured by CO2 evolution, after 28 days.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is readily biodegradable. 70 - 100% degradation in water, measured by CO2 evolution, after 28 days.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Name	Result
Benzenesulfonic acid, C10-16- alkyl derivatives	Under test conditions no biodegradation observed.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Citric acid	Low potential for bioaccumulation (BCF: 3.2 L/kg).
Hydrogen chloride	Not expected to bioaccumulate (log Kow = -2.65).
Ethane-1,2-diol	Bioaccumulation in organisms is not to be expected (log Kow: -1.36).
2-Butoxyethanol	Not expected to bioaccumulate (log Kow = 0.83).
Ethylene oxide	Low potential for bioaccumulation ($logKow = -0.3$).
1,4-dioxane	Does not accumulate in aquatic organisms (mean BCF: 0.45).
Alcohols, C9-11, branched and linear, ethoxylated	The substance has low potential for bioaccumulation. Bioaccumulation in organisms is negligible, due to biotransformation and excretion of alcohol ethoxylates. BCF: 237 L/kg

Mobility in Soil

Product Data: No data available.

|--|

Name	Result
Ethane-1,2-diol	Adsorption to the solid soil phase is not expected.
1,4-dioxane	Significant adsorption to solid soil phase is not expected (calculated log Koc: 0.51 at 25 °C).
Alcohols, C9-11, branched and linear, ethoxylated	Moderately mobile (log Koc: 1.575 - 2.365).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Citric acid	Substance is not PBT	
Orthophosphoric Acid	The PBT assessment does not apply to inorganic substances.	
Hydrogen chloride	The substance is not PBT.	
Ethane-1,2-diol	The substance is not PBT.	
2-Butoxyethanol	The substance is not PBT.	
Ethylene oxide	This substance is not PBT.	
1,4-dioxane	This substance is not PBT.	
Alcohols, C9-11, branched and linear, ethoxylated	The substance is not PBT.	
Sodium Xylenesulfonate	The substance is not PBT.	
vPvB assessment:		
Citric acid	Substance is not vPvB	
Orthophosphoric Acid	The vPvB assessment does not apply to inorganic substances.	
Hydrogen chloride	The substance is not vPvB.	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023

Revision date: 03.08.2023

Bay and Wall Cleaner

Ethane-1,2-diol	The substance is not vPvB.
2-Butoxyethanol	The substance is not vPvB.
Ethylene oxide	This substance is not vPvB.
1,4-dioxane	This substance is not vPvB.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is not vPvB.
Sodium Xylenesulfonate	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1760			
UN Proper Shipping Name	CORROSIVE LIQUID, N.O.S HYDROCHLORIC ACID, PHOSPHORIC ACID			
UN Transport Hazard Class(es)	8			
Packing Group	Ш			
Environmental Hazards	None			
Special Precautions for User	None			

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023 Revision date: 03.08.2023

Bay and Wall Cleaner

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances:

7647-01-0	Hydrogen chloride	Listed
75-21-8	Ethylene oxide	Listed

SARA Section 313 Toxic Chemicals:

7647-01-0	Hydrogen chloride	Listed
107-21-1	Ethane-1,2-diol	Listed
111-76-2	2-Butoxyethanol	Listed
75-21-8	Ethylene oxide	Listed
123-91-1	1,4-dioxane	Listed

CERCLA:

7664-38-2	Orthophosphoric Acid	Listed	5000 Lbs.
7647-01-0	Hydrogen chloride	Listed	5,000 Lbs.
107-21-1	Ethane-1,2-diol	Listed	5000 lb
111-76-2	2-Butoxyethanol	Listed	N/A
75-21-8	Ethylene oxide	Listed	10 lbs
123-91-1	1,4-dioxane	Listed	100 lbs

RCRA:

75-21-8	Ethylene oxide	Listed	U115
123-91-1	1,4-dioxane	Listed	U108

Section 112(r) of the Clean Air Act (CAA):

7647-01-0	Hydrogen chloride	Listed
75-21-8	Ethylene oxide	Listed

Massachusetts Right to Know:

7664-38-2	Orthophosphoric Acid	Listed
7647-01-0	Hydrogen chloride	Listed
107-21-1	Ethane-1,2-diol	Listed
75-21-8	Ethylene oxide	Listed
123-91-1	1,4-dioxane	Listed
111-76-2	2-Butoxyethanol	Listed

New Jersey Right to Know:

7664-38-2	Orthophosphoric Acid	Listed
7647-01-0	Hydrogen chloride	Listed
107-21-1	Ethane-1,2-diol	Listed
75-21-8	Ethylene oxide	Listed
123-91-1	1,4-dioxane	Listed

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 03.08.2023 Revision date: 03.08.2023

Bay and Wall Cleaner

	111-76-2	2-Butoxyethanol	Listed			
Ne	New York Right to Know:					
	7664-38-2	Orthophosphoric Acid	Listed			
	7647-01-0	Hydrogen chloride	Listed			
	107-21-1	Ethane-1,2-diol	Listed			
	75-21-8	Ethylene oxide	Listed			
	123-91-1	1,4-dioxane	Listed			
	111-76-2	2-Butoxyethanol	Listed			

Pennsylvania Right to Know:

7664-38-2	Orthophosphoric Acid	Listed
7647-01-0	Hydrogen chloride	Listed
107-21-1	Ethane-1,2-diol	Listed
75-21-8	Ethylene oxide	Listed
123-91-1	1,4-dioxane	Listed
111-76-2	2-Butoxyethanol	Listed

California Proposition 65:

WARNING: This product can expose you to 1,4-dioxane; which is known to the State of California to cause cancer; and Ethane-1,2-diol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

WARNING: This product can expose you to Ethylene oxide; which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0 HMIS: 0-0-0

Initial Preparation Date: 03.08.2023

End of Safety Data Sheet

Page 18 of 18